



WindARMOR™ Portable Litter Fence

PLF2415 Specification

Structural Frame

Base: 7" x 5" x 1/4" structural steel tubing
Upright: 4" x 2" x 3/16" structural steel tubing
Crossmember: 4" x 2" x 3/16" structural steel tubing

Width: 24 ft.
Height: 15 ft.
Depth: 7.5 ft. – 11.5 ft. (with outriggers horizontal)
Weight: 3600 lbs

Enclosure

Back Mesh: 1.25 inch 16 ga. steel welded wire mesh with black vinyl coating
Side Mesh: 1.25 inch 16 ga. steel welded wire mesh with black vinyl coating
Top Canopy Mesh: 1.12 inch black UVS polypropylene

Adjustable Lifting Brackets

The PLF is equipped with adjustable brackets to accommodate blades on most landfill equipment. The blade of existing equipment simply hooks under the brackets and the PLF can be lifted and moved. The standard lifting bracket can be installed on the front or back. Or, for maximum accessibility, an optional dual access lift bracket is available to lift at the front and the back.

Vertical adjustment: 87 - 105 inches
Horiz. adjustment: 16 inches

Paint: High Solids Industrial Enamel Finish Coat

Warranty: Three Year Warranty

Performance, Features and Benefits

- Capable of withstanding winds of 65+ mph without overturning
- Configurable Lifting Bracket design allows access for handling from front, back or both
- No-Gap design provides tight alignment between sections to contain litter for complete perimeter protection
- Complete surround is 16 ga. steel welded wire mesh with vinyl non-stick coating
- Outriggers adjust independently and can drop below grade for optimum stability on workface
- Backed by Southwestern Sales Co. superior customer support & 40 years of manufacturing excellence

